


# 丸ワッシャー(平座金)

●=即日出荷  
▼=一両日出荷

材質					鋼製							黄銅	SUS製		
表面処理等 ⇒					生地	三価ホワイト	ユニクロ	クロメート	黒色クロメート	溶融亜鉛	S45C		生地	ニッケル	SUS304
呼び	内径(mm)	外径(mm)	厚み(mm)								生地	クロメート			
2	2.2	5	0.3	ISO		▼									
2.3	2.5	6.5	0.5	ISO		▼									
2.5	2.7	6.5	0.5	ISO		▼									
2.6	2.8	6.5	0.5	ISO		▼									
3	3.3	8	0.5	JIS	●	●	●	●	●			●	●	●	
	3.2	7	0.5	ISO	●	▼		●				▼	▼	▼	
4	4.5	10	0.8	JIS	●	●	●	●	●			●	●	●	
	4.3	9	0.8	ISO	●	▼		●				▼	▼	●	
5	5.5	12	0.8	JIS	●	●	●	●	●			●	●	●	
	5.3	10	1.0	ISO	●	▼		●				▼	▼	●	
6	6.5	13	1.0	JIS	●	●	●	●	●			●	●	●	
	6.4	12.5	1.6	ISO	●	▼		●				▼	▼		
	6.4	12.5	1.5											●	
	6.5	14	2.3	HT							●				
8	8.5	18	1.6	JIS	●	●	●	●	●	●		●	●		
	8.5	17	1.6	ISO	●	●		●				▼	▼		
	8.5	18	1.2											●	
	8.5	17	1.5											●	
	8.5	18	2.3	HT							●	▼			
10	10.5	22	1.6	JIS	●	●	●	●	●	●		●	●		
	10.5	21	2.0	ISO	●	●		●				▼	▼	●	
	10.5	22	1.5											●	
	10.5	22	3.2	HT							●	▼			
12	12.5	26	2.3	JIS	●	●	●	●	●	●		●	●		
	13	24	2.5	ISO	●	●		●						●	
	12.5	26	2.0											●	
	13	26	3.2	HT							●	▼			
14	15	30	2.6	JIS	●	●	●	●				●	▼		
	15	28	2.5	ISO	●	▼		●						●	
	15	30	2.0											●	
	15	30	3.2	HT							●	▼			
16	17	32	2.6	JIS	●	●	●	●	▼	●		●	▼		
	17	30	3.0	ISO	●	▼		●						●	
	17	32	2.0											●	
	17	32	4.5	HT							●	▼			
18	19	36	2.6	JIS	●	●	●	●							
	19	34	3.0	ISO	●	▼		●						●	
	19	36	2.5											●	
	19	36	4.5	HT							●				
20	21	40	3.2	JIS	●	●	●	●		●		●	▼		
	21	37	3.0	ISO	●	▼		●						●	
	21	40	3.0											●	
	21	40	4.5	HT							●	▼			
22	23.5	44	3.2	JIS	●	●	●	●		●		●	▼		
	23	39	3.0	ISO	●	▼		●						●	
	24	44	3.0											●	
	23	44	6.0	HT							●	▼			

SUS製の商品はSUS304相当品となっております。

<p>お問い合わせフォーマット</p> <p><a href="http://www.ikekin.co.jp/contents/inquiry/index.html">http://www.ikekin.co.jp/contents/inquiry/index.html</a></p>	<p>電話でのお問い合わせ</p> <p> 0120-119-810</p>
--	--

# 丸ワッシャー(平座金)

●=即日出荷 ▼=一両日出荷

材質					鋼製							黄銅	SUS製		
表面処理等 ⇒					生地	三価ホワイト	ユニクロ	クロメート	黒色クロメート	溶融亜鉛	S45C		生地	ニッケル	SUS304
											生地	クロメート			
呼び	内径(mm)	外径(mm)	厚み(mm)												
24	25.5	48	4.0	JIS	●	●	●	●	●			●			
	25	44	4.0	ISO	●	▼		●						●	
	25.5	48	3.0											●	
	25	48	6.0	HT						●	▼				
27	28.5	52	4.0	JIS	●		●	●							
	28	50	4.0	ISO	●	▼		●						●	
	28.5	52	6.0	HT						●					
30	31.5	58	4.5	JIS	●		●	●						●	
	31	56	4.0	ISO	●	▼		●						●	
	33	58	6.0	HT						●	▼				
33	34.5	62	4.5	JIS	●		●	●						●	
	34	60	5.0	ISO	●			●						●	
	36	62	6.0	HT						●					
36	38	68	5.0	JIS	●		●	●						●	
	37	66	5.0	ISO	●			●						●	
	39	68	6.0	HT						●					
39	41	72	5.0	JIS	●										
	40	72	6.0	ISO	●										
	42	78	6.0	HT						●					
42	44	78	6.0	JIS	●		●								
	43	78	7.0	ISO	●										
	45	78	6.0	HT						●					
45	47	82	6.0	JIS	●										
	46	85	7.0	ISO	●										
	48	82	6.0	HT						●					
48	50	88	6.0	JIS	●										
	50	92	8.0	ISO	●										
	51	86	6.0	HT						●					
52	54	95	6.0	JIS	●										
	54	98	8.0	ISO	●										
	55	95	6.0	HT						●					
56	58	105	9.0	ISO	▼										
60	62	110	9.0	ISO	▼										
64	66	115	9.0	ISO	▼										
68	70	120	10.0	ISO	▼										
72	74	125	10.0	ISO	▼										
76	78	132	10.0	ISO	▼										
80	82	140	12.0	ISO	▼										
W3/8	10.5	25	1.5	W										●	
W1/2	13.5	26	2.3	JIS	●	●	●	●							
	13.5	26	2.0											●	
	13.5	32	2.0	W										●	

SUS製の商品はSUS304相当品となっております。

## イケキンカスタマーセンター

### お問い合わせフォーマット

お客様のご意見・ご質問・ご要望などをお受けしています。  
お気軽にご利用下さい。

<http://www.ikekin.co.jp/contents/inquiry/index.html>

### 電話でのお問い合わせ

土日祝日を除く月～金曜日  
9:00～17:00

 0120-119-810