

ノルトロックワッシャー寸法表

高耐食性ステンレス製

正規
代理店



池田金属工業株式会社
<http://www.ikekin.co.jp>

材	料	: 254SMO®(SUS 312L 相当)	材	料	規	格	: EN 1.4547			
硬	さ	: ≥ 600HV0.05 / 55.2HRC (近似値的換算)	ボ	ルト	強	度	区	分	: A4-80 まで	
耐	腐	食	性	: PRE 値 45	対	応	温	度	帯	: -160℃ ~ 500℃

メートル	ボルトサイズ インチ	製品 型番	Øi [mm]	Øo [mm]	厚み T [mm]	100 組当たりの 概算重量 [kg]	小箱入数 [組]	
	M3	#5	NL3ss-254	3.4	7.0	2.2	0.04	200
	M3.5	#6	NL3.5ss-254	3.9	7.6	2.2	0.04	200
	M3.5	#6	NL3.5spss-254	3.9	9.0	2.2	0.07	200
	M4	#8	NL4ss-254	4.4	7.6	2.2	0.04	200
	M4	#8	NL4spss-254	4.4	9.0	2.2	0.07	200
	M5	#10	NL5ss-254	5.4	9.0	2.2	0.06	200
	M5	#10	NL5spss-254	5.4	10.8	2.2	0.11	200
	M6		NL6ss-254	6.5	10.8	2.2	0.09	200
	M6		NL6spss-254	6.5	13.5	2.0	0.16	200
		1/4"	NL1/4"ss-254	7.2	11.5	2.2	0.09	200
		1/4"	NL1/4"spss-254	7.2	13.5	2.2	0.15	200
	M8	5/16"	NL8ss-254	8.7	13.5	2.0	0.12	200
	M8	5/16"	NL8spss-254	8.7	16.6	2.2	0.22	200
		3/8"	NL3/8"ss-254	10.3	16.6	2.0	0.19	200
		3/8"	NL3/8"spss-254	10.3	21.0	2.2	0.38	200
	M10		NL10ss-254	10.7	16.6	2.0	0.18	200
	M10		NL10spss-254	10.7	21.0	2.2	0.37	200
	M11	7/16"	NL11ss-254	11.4	18.5	2.2	0.26	200
	M12		NL12ss-254	13.0	19.5	2.0	0.23	200
	M12		NL12spss-254	13.0	25.4	3.2	0.83	100
		1/2"	NL1/2"ss-254	13.5	19.5	2.0	0.23	200
		1/2"	NL1/2"spss-254	13.5	25.4	3.2	0.80	100
	M14	9/16"	NL14ss-254	15.2	23.0	3.0	0.49	100
	M14	9/16"	NL14spss-254	15.2	30.7	3.2	1.13	100
	M16	5/8"	NL16ss-254	17.0	25.4	3.0	0.59	100
	M16	5/8"	NL16spss-254	17.0	30.7	3.2	1.13	100
	M18		NL18ss-254	19.5	29.0	3.2	0.80	100
	M18		NL18spss-254	19.5	34.5	3.2	1.56	100
		3/4"	NL3/4"ss-254	20.0	30.7	3.2	0.96	100
		3/4"	NL3/4"spss-254	20.0	39.0	3.2	2.14	100
	M20		NL20ss-254	21.4	30.7	3.0	0.83	100
	M20		NL20spss-254	21.4	39.0	3.2	1.98	100
	M22	7/8"	NL22ss-254	23.4	34.5	3.2	1.19	100
	M22	7/8"	NL22spss-254	23.4	42.0	3.2	2.44	50
	M24		NL24ss-254	25.3	39.0	3.2	1.65	100
	M24		NL24spss-254	25.3	48.5	4.5	4.47	50
		1"	NL1"ss-254	27.9	39.0	3.2	1.42	100
		1"	NL1"spss-254	27.9	48.5	5.6	5.30	50
	M27		NL27ss-254	28.4	42.0	5.8	3.10	50
	M27		NL27spss-254	28.4	48.5	5.8	5.34	25
	M30	1 1/8"	NL30ss-254	31.4	47.0	5.8	4.04	50
	M33	1 1/4"	NL33ss-254	34.4	48.5	5.8	3.86	25
	M36	1 3/8"	NL36ss-254	37.4	55.0	5.8	5.50	25
	M39	1 1/2"	NL39ss-254	40.4	58.5	5.8	6.74	25