

SUS316

材 質：SUS316 材 料 規 格：UNS S31600
 サ イ ズ：M3－M12 対 応 温 度 帯：～425℃
 特 色：耐食性 / 耐薬品性 ※記載のないサイズは受注生産



PART.NO.	サイズ		自由巻数	自由外径	ドリルサイズ
	径	長さ			
TL05032Y	M3-0.50	1D	3.750	3.65-4.35	3.1
TL05033Y		1.5D	6.375		
TL05034Y		2D	8.875		
TL05042Y	M4-0.70	1D	3.625	4.90-5.60	4.2
TL05043Y		1.5D	6.125		
TL05044Y		2D	8.625		
TL05052Y	M5-0.80	1D	4.125	6.00-6.80	5.2
TL05053Y		1.5D	6.875		
TL05054Y		2D	9.625		
TL05062Y	M6-1.00	1D	4.000	7.25-7.95	6.3
TL05063Y		1.5D	6.750		
TL05064Y		2D	9.500		
TL05082Y	M8-1.25	1D	4.500	9.80-10.35	8.4
TL05083Y		1.5D	7.375		
TL05084Y		2D	10.250		
TL05102Y	M10-1.50	1D	4.875	11.95-12.50	10.5
TL05103Y		1.5D	8.000		
TL05104Y		2D	11.125		
TL05122Y	M12-1.75	1D	5.000	14.20-15.00	12.5
TL05123Y		1.5D	8.250		
TL05124Y		2D	11.500		